



Adjustable GPM Handline Nozzle (5-10-24-40 gpm) Part No. MA10P

DESCRIPTION

The Chemguard Adjustable Gallonage Handline Nozzle is an adjustable gallonage device that provides the operator with a great degree of flexibility. The flow rate can be manually adjusted during operation without shutting down the nozzle. It has been designed to give a constant flow whether the stream pattern selected is on straight stream, power cone or wide angle fog. The nozzles are manufactured in "Chemlite"™ (anodized black aluminum) or brass.

FEATURES

- Four (4) flow selection ranges
- Extra large gallonage selection ring
- Reliable spinning turbine teeth - This feature provides excellent dispersion of the water stream in either the wide angle fog or the power cone mode. Finer water droplets for greater heat absorption are generated.
- Flush mechanism - The operator can flush debris from within the nozzle without shutting down.
- Large rubber bumper - The bumper is ribbed to allow fire fighters, while wearing gloves, to change water stream pattern selections without shutting down. It also protects the nozzle if inadvertently dropped.
- Large rubber handle - A large handle controls the on / off function of the nozzle. It is designed to enable the fire fighter to operate it while wearing gloves.
- Durable Chrome Plated Ball Shut Off - full flow type

- Removable pistol grip
- Dual trunion drive on ball shut off. This provides smoother shut off action and less maintenance.
- Conforms to all NFPA-1964 standards
- Suitable for use with water, AFFF, AR-AFFF, Class A foam solutions and in-line eductors.
- Nozzle supplied with 1" female swivel NST inlet as standard
- Option - other inlet threads available

NOZZLE FLOW INFORMATION 100 PSI RATED STANDARDS

(See charts at end of this section).

ORDERING INFORMATION

MODEL	LENGTH	WEIGHT
MA10P CHEMLITE	9-1/8 in.	2.5 lbs

