



Adjustable GPM Handline Nozzle (95-125-150-200-250 gpm) Part No. MA25P

DESCRIPTION

The high-range Chemguard handline nozzle is a multi-gallonage device which gives the operator a great degree of flexibility. The flow rate can be manually adjusted during operation without having to shut the nozzle down. It has been designed to give a constant flow whether the stream pattern selected is on straight stream, power cone or wide angle fog. The nozzle is manufactured in "Chemlite"™ (anodized black aluminum).

FEATURES

- Five (5) flow selection ranges
- Extra large gallonage selection ring
- Reliable spinning turbine teeth - This feature provides excellent dispersion of the water stream in either the wide angle fog or the power one mode. Finer water droplets for greater heat absorption are generated.
- Flush mechanism - The operator can flush debris from within the nozzle without shutting down.
- Large rubber bumper - The bumper is ribbed to allow the fire fighters, while wearing gloves, to change water stream pattern selections without shutting down. It also protects the nozzle if advertently dropped.
- Large rubber handle - A large handle controls the on/off function of the nozzle. It is designed to enable the fire fighter to operate it while wearing gloves.
- Dual trunion drive on ball shut off - This provides smoother shut off action and less maintenance.

- Conforms to all NFPA-1964 standards
- Durable Chrome Plated Ball Shut Off - full flow type
- Removable pistol grip
- Nozzle supplied with 2½" Female NST swivel inlet as standard
- Suitable for use with water, In-Line eductor, AFFF, AR-AFFF and Class A foam solutions

NOZZLE FLOW INFORMATION 100 PSI RATED STANDARDS

(See charts at end of this section).

ORDERING INFORMATION

MODEL	LENGTH	WEIGHT
MA25P	11 in.	6.2 lbs.

