



Constant Flow Handline Nozzle (95 gpm) Part No. SB95P

DESCRIPTION

The Constant Gallonage Chemguard Handline Nozzle is designed to provide a constant flow whether on straight stream or fog pattern which provides increased fire fighting safety. The nozzles are manufactured in brass.

FEATURES

- Reliable spinning turbine teeth - This feature provides excellent dispersion of the water stream in either the wide angle fog or the power cone mode. Finer water droplets for greater heat absorption are generated.
- Flush mechanism - The operator can flush debris from within the nozzle without shutting down.
- Large rubber bumper - The bumper is ribbed to allow fire fighters, while wearing gloves, to change water stream pattern selections without shutting down. It also protects the nozzle if dropped.
- Large rubber handle - A large handle that controls the on/off function of the nozzle. It is designed to enable the fire fighter to operate it while wearing gloves.
- Dual trunion drive on ball shut off – provides smoother shut off action and less maintenance.
- Conforms to all NFPA-1964 standards
- Durable Chrome Plated Ball Shut Off - full flow type

- Suitable for use with water, AFFF, AR-AFFF or Class A foam solution and the 95 gpm in-line eductor
- Removable pistol grip
- Nozzle supplied with 1½" swivel female NST inlet as standard
- Option - other inlet threads available

NOZZLE FLOW INFORMATION 100 PSI RATED STANDARDS

(See charts at end of this section).

ORDERING INFORMATION

MODEL	LENGTH	WEIGHT
SB95P	8 3/4"	6 ½ lbs.

