



Automatic Flow Handline Nozzle (60-200 gpm) Part No. AA15P

DESCRIPTION

The Chemguard automatic handline nozzle reacts automatically to changes in flow. The flow is delivered in an efficient manner at a constant pressure throughout the flow range of the nozzle. The nozzle will give a constant flow whether the stream pattern selected is on straight stream, power cone or wide angle fog. The nozzle is manufactured in "Chemlite"™ (anodized black aluminum).

FEATURES

- Maintains a consistent operating pressure over a wide flow range
- Reliable spinning turbine teeth - This feature provides excellent dispersion of the water stream in either the wide angle fog or the power cone mode. Finer water droplets for greater heat absorption are generated.
- Flush mechanism - The operator can flush debris from within the nozzle without shutting down.
- Large rubber bumper - The bumper is ribbed to allow the fire fighters, while wearing gloves, to change water stream pattern selections without shutting down. It also protects the nozzle if inadvertently dropped.
- Large rubber handle - A large handle controls the on / off function of the nozzle. It is designed to enable the fire fighters to operate it while wearing gloves.
- Dual trunion drive on ball shut off - This provides smoother shut off action and less maintenance.
- Conforms to all NFPA-1964 standards

- Durable Chrome Plated Ball Shut Off - full flow type
- Removable Pistol Grip
- Nozzle supplied with 1½" Female NST inlet as standard
- Suitable for use with water, In-Line eductors, AFFF, AR-AFFF and Class A Foam solutions

NOZZLE FLOW INFORMATION 100 PSI RATED STANDARDS

(See charts at end of this section).

ORDERING INFORMATION

MODEL	LENGTH	WEIGHT
AA15P	12 in.	6 lbs.

