



Synthetic Wetting Agent CHEMWET

DESCRIPTION

Chemguard CHEMWET is a highly concentrated wetting and penetrating agent, which reduces the surface tension of water. The reduction of the surface tension allows for quicker extinguishment and reducing water requirements. CHEMWET is designed for proportioning at 0.05% (one gallon of CHEMWET to 2,000 gallons of water). The CHEMWET formula contains anti-rust and anti-scaling agents as well as friction reducers, which improves the longevity of storage tanks and increases the performance of application. The penetration rate of CHEMWET is 350% to 400%.

FEATURES

- Excellent wetting characteristics when used in combatting Class A type fuel fires.

PROPORTIONING

Chemguard CHEMWET is suitable for use with the following types of proportioning equipment:

- Pre-mix
- In-line eductor

TYPICAL PROPORTIONING

Appearance	Colorless liquid
Specific Gravity	1.05
pH	7-8
Viscosity	25 cps

ENVIRONMENTAL IMPACT

Chemguard CHEMWET is biodegradable, low in toxicity and can be treated in sewage treatment plants. CHEMWET concentrate is not manufactured with raw materials that are listed as reportable on any Federal Register.

STORAGE

CHEMWET is fully synthetic product. If kept in the original manufacturer's supplied container and storage within the temperature range 35 F - 120 F an indefinite shelf life can be expected. If frozen, thawing will render CHEMWET completely serviceable again.

ORDERING INFORMATION

Part No. CWP	5 Gal. Pail (19 l)
Part No. CWD	55 Gal. Drum (208 l)

SHIPPING WEIGHT

5 Gal. Plastic Pail	44 lbs.
55 Gal. Plastic Drum	485 lbs.

